

Certificate of Compliance

Certificate: 1880726 (222965)

Master Contract: 229265

Project: 2096747

Date Issued: 2008/10/21

Issued to: Munters Italy S.p.A.
Strada Piani, 2
Chiusavecchia, Imperia 18027
Italy
Attention: Pierangelo Oda

The products listed below are eligible to bear the CSA Mark shown with adjacent indicators 'C' and 'US'



Issued by: Andy Vella

Authorized by: Renzo Pupulin, C.E.T., Product Group Manager

Renzo Pupulin

PRODUCTS

- CLASS 6421 01** - FUEL BURNING EQUIPMENT (OIL) - Units - Commercial/Industrial
- CLASS 2902 83** - COMMERCIAL HEATERS (GAS) - Indirect Construction Use-Certified to U.S. Standards
- CLASS 2902 03** - COMMERCIAL HEATERS (GAS) - Indirect Construction Use
- CLASS 6421 81** - FUEL BURNING EQUIPMENT (OIL) - Units - Commercial/Industrial - Certified to US Standards

HELIOS (400,500,750)C, AIRFLOW 400, HEL (110,150,200) CO and AFW 110 XO Series

APPLICABLE REQUIREMENTS

The 'C' and 'US' indicators adjacent to the CSA Mark signify that the product has been evaluated to the applicable CSA and ANSI/UL Standards, for use in Canada and the U.S., respectively. This 'US' indicator includes products eligible to bear the 'NRTL' indicator. NRTL, i.e. National Recognized Testing Laboratory, is a designation granted by the U.S. Occupational Safety and Health Administration (OSHA) to laboratories which have been recognized to perform certification to U.S. Standards.



Certificate: 1880726 (222965)

Master Contract: 229265

Project: 2096747

Date Issued: 2008/10/21

ANSI Z83.7-2000 / CSA 2.14 - 2000 Gas-Fired Construction Heaters

CSA B140.8-1967(R2001) Portable Industrial Oil-Fired Heaters

UL 733 , 4th Edition Oil-Fired Air Heaters and Direct-Fired Heaters

MARKINGS

All Models comply with the marking requirements of the applicable standards. Copies of all labels are attached in the descriptive drawing section of the Report. All markings must use the following materials and specs: AVERY 710 Clear Polyester; For indoor/outdoor applications; Service temperature range of -40°C to 150°C.

CSA/ANSI Class IIIA-2 - Permanent Label