

MSC: Munters Simplex Curtain

Munters Simplex Curtain is developed for use in Dairy, Swine and Poultry installations. The curtain combines ventilation requirements with ease of operation and value for money. The curtain can replace an entire outer wall (or parts of) on the building.

The curtain is installed directly on the wall, ensuring that any draft under the curtain and into the shed is avoided.

A principal feature of the curtain is that it is coiled on the bottom profile so that it can be rolled down completely, thus providing a full view of the surroundings, or alternatively it can be closed completely or rolled down to any point between fully closed and fully open.

Nordvestvej, 3 - 9600 Aars, Denmark / Phone +45 986 233 11 / Fax +45 986 213 54 / www.munters.dk/agro

Munters A/S





Product description

Munters Simplex Curtain is manufactured in heavy duty, UV resistant PVC coated high tenacity polyester. The light grey color ensures optimal light transmission. The curtain is anti-static and will repel dirt (sand, straw, dust). The curtain rolls on an extruded aluminum profile.

As safety against strong winds, specially designed wind pipes are installed at intervals of 2 meters (recommended distance – distance varies depending on opening height). The wind pipes are made of galvanized iron with an outer plastic pipe – the latter to minimize wear and tear on both wind pipe and curtain. Wind pipes are installed on the outside and inside of the curtain, acting as a guide for the curtain.

As an alternative to wind pipes, Munters Simplex Curtain can be delivered with rope instead. The rope is installed in the front and rear of the curtain and serves as safety against strong winds as well as a guide for the curtain in the same way as wind pipes. The rope is secured by means of eye bolts which are screwed into the top and bottom timber. The rope follows a "V" shaped pattern along the entire length of the curtain.

To minimize draft from the sides of the curtain, specially designed wind screens are installed on both sides of each curtain section. The curtain is equipped with a stainless steel wire pulling system, which can be operated vertically by a winch motor. It is possible to choose between semi-automatic operation, where you decide when the curtain moves up or down, or a fully automated operation, where the curtain is regulated by the Munters NaturalCenter/Master climate controller combined with a weather station.

Tecnical data

Max height	3 meter
Max length	50 m (max 150 m ² per section)
Power	1 phaset 230V
Function	Roll from top down
Accessories	Automatic regulation



Australien Munters Pty Limited, Phone +61 2 8843 1594, Brasilien Munters Brasil Industria e Comercio Ltda, Phone +55 41 3317 5050, Canada Munters Corporation Mason, Phone +1 517 676 7070, kina Munters Air Treatment Equipment (Beijing) Co. Ltd, Phone +86 10 80 418 000, Denmark Munters A/S, Phone +45 9862 3311, India Munters India, Phone +91 20 3052 2520, Indonesien Munters, Phone +62 818 739 235, Italien Munters Italy S, p.A., Chiusavecchia, Phone +39 0183 52 11, Japan Munters K.K., Phone +81 3 5970 0021, Korea Munters Korea Co. Ltd., Phone +82 2 761 8701, Mexico Munters Mexico, Phone +52 818 262 54 00, Singapore Munters Pte Ltd., Phone +65 744 6828, Sydafrita & landene syd for Scharo Munters (Pty) Ltd., Phone +27 11 997 2000, Spanien Munters Spain S.A., Phone +34 91 640 09 02, Sverige Munters AB, Phone +46 8 626 63 00, Thailand Munters Co. Ltd., Phone +66 2 642 2670, Tyrkief Munters Form Endüstri Sistemleri A,S, Phone +90 262 751 3750, USA. Munters Italy S, p.A., Chiusavecchia Phone +151 767 67070, Vietnam Munters Vietnam, Phone +84 8 3825 6838, Export & other countries Munters Italy S, p.A., Chiusavecchia Phone +39 0183 52 11

Munters reserves the right to make alterations to specifications, quantities, etc., for production or other reasons, subsequent to publication.
© Munters, 2015



Your closest distributor