







Table: Minimum fans from Munters						
	Series	Material	Number	Flow at 20Pa or 0.08'' m3/hour(cfm)	Energy at 0 Pa, 0'' m3/h/W (cfm/W)	Speed control
Denmark	<b>TU</b> <a href="#">Go to web</a> 	Corrosion resistant	TU600 (0.9hp) TU800 (0.9hp)	12090(7116) 19364(11397)	28.4(16.7) 34.0(20.9)	Munters Drive Direct drive  Variable speed control
		Polyethylene housing  Insulated damper/ shutter				
Italy	<b>EM</b> <a href="#">Go to web</a>  <b>ED HE</b> <a href="#">Go to web</a> 	Galvanized steel with Munters Protect or stainless steel	EM30 (0.75hp) EM36 (1.0hp) EM50n(1hp) <sup>1</sup>	13410(7890) 20750(12210) 31594(18600)	20.2(11.8) 18.5(10.9) 34.5(20.3)	Belt Single or multi speed
		3 years extended warranty of corrosion perforation of metal housing, shutter blades and propeller	ED24HE <sup>2</sup> (0.5hp) ED30HE <sup>2</sup> (0.5hp) ED36HE <sup>2</sup> (0.75hp)	8800(5180) 13700(8080) 18200(10700)	17.3(10.2) 22.1(13.0) 30.3(17.8)	Direct drive
USA	<b>VX</b> <a href="#">Go to web</a> 	Corrosion resistant fiber glass housing	VX36(0.5hp) <sup>1,5</sup> VX36(1hp) <sup>1,5</sup>	18496(10880) 24752(14560)	29.1(17.1) 19.9(11.7)	Belt
		Cast aluminum blade	VX48 <sup>1</sup> VX51(1hp)	37208(21900) 41626(24500)	34.8(20.5) 40.9(24.1)	Munters Drive
	<b>DDVX</b> <a href="#">Go to web</a> 	Plastic shutter	DDVX14 <sup>1,3</sup> DDVX16 <sup>1,3</sup> DDVX18 <sup>1</sup> DDVX24 <sup>1</sup> DDVX26 <sup>1,3</sup> DDVX36(0.5hp) <sup>1,5</sup>	3050(1803) 5033(2990) 6900 (4080) 9700(5650) 11610(6870) 18564(10920)	20.2(11.9) 21.3(12.5) 18.9(11.1) 28.7(16.9) 27.7(16.3) 28.2(16.6)	Direct drive  Variable speed control
		<b>WF</b> <a href="#">Go to web</a> 	Galvanized steel fan Cast aluminum drive. 7 year bearing warranty) Heavy duty galvanized steel propeller. Shutter in aluminum (TCJ) or plastic (TCP)	WF54 <sup>1,4</sup>	43771(25900)	40.0(23.5)

**Notes:**

Note1: Airflow measured at 25Pa (0.10'')

Note2: Airflow measured at 12Pa (0.05'')

Note3: Single phase motor

Note4: Three Phase, 460 Volt motor

Note5: Previous called AT Fan

All the fans have shown in the table have additional versions with different motors (different hp).

The EM, ED HE and VX fans are also available in bigger size for maximum ventilation.